



Erläuterungen siehe Praxisinfos auf den Seiten 6 und 86!

## GEFAHRSTOFFSTATION FÜR FÄSSER AUS PE


### Zur Lagerung von wassergefährdenden und aggressiven Medien im Innen- oder Außenbereich

- ◆ Rotationsgeformte Konstruktion gelb, mit Wannenkörper aus PE schwarz
- ◆ Umlaufende Stabilisierungsrippen
- ◆ Unterfahrbarkeit für innerbetrieblichen Transport
- ◆ Stellebene aus PE-Lochplatte
- ◆ Wetterschutz durch PE-Jalousie schwarz, abschließbar mit kundenseitigem Vorhängeschloss
- ◆ Dokumentenablage in der Seitenwand serienmäßig
- ◆ Auffangwannen mit allgemeiner bauaufsichtlicher Zulassung des DIBt Berlin
- ◆ Anlieferung als Bausatz zur einfachen Selbstmontage vor Ort

Zul.-Nr.: Z-40.22-380



**PE-ST-2,  
Artikel-Nr. P70-2052-A,  
mit optionalem Regal-Set**



**Integrierte  
Dokumentenablage**



**PE-ST-2,  
Artikel-Nr. P70-2052-A**



**PE-ST-4,  
Artikel-Nr. P70-2053-A**



**PE-ST-45,  
Artikel-Nr. P70-2054-A**



**Sicherheitslagerstationen  
für 200-Liter-Fässer finden  
Sie auf Seite 148!**

Typenbezeichnung	PE-ST-2	PE-ST-4	PE-ST-45
Außenmaße B x T x H in mm	1500 x 1100 x 2110	1560 x 1790 x 2110	1560 x 1790 x 2110
Innenmaße B x T x H in mm	1220 x 750 x 1330	1220 x 1380 x 1510	1220 x 1380 x 1330
Auffangvolumen in Liter	236	242	450
Kapazität à 200-Liter-Fass	2 direkt auf PE-Lochplatte oder Europalette	4 direkt auf PE-Lochplatte oder Chemiepalette	4 direkt auf PE-Lochplatte oder Chemiepalette
Max. Belastung in kg	500	1000	1000
<b>Artikel-Nr., mit PE-Lochplatte</b>	<b>P70-2052-A</b>	<b>P70-2053-A</b>	<b>P70-2054-A</b>

Zubehör	Artikel-Nr.
Regal-Set zur Lagerung von Kleingebinden oder Kanistern mit 2 höhenverstellbaren Gitterrost-Ebenen, B x T x H in mm = 1060 x 635 x 1150, Tragkraft je Ebene 200 kg	<b>P70-2056-A</b>



Explanations see practical informations on page 6 and 84!

## PE STATION FOR DRUMS


### For the storage of water-endangering and aggressive media indoors and outdoors

- ◆ Rotationally-molded PE-construction yellow, with black PE-sump tray
- ◆ Circumferential stabilizing ribs
- ◆ Ground clearance for internal transport
- ◆ PE perforated plate
- ◆ Weather protection with black PE louvre-door, lockable with padlock on customer side
- ◆ Document tray in the side wall as standard
- ◆ Sump trays with general technical approval DIBt Berlin
- ◆ Delivered as a kit for easy self-assembly on site

Approval-No.: Z-40.22-380



**PE-ST-2,**  
Article no. P70-2052-A,  
with optional shelf set



**Integrated document storage**



**PE-ST-2,**  
Article no. P70-2052-A



**PE-ST-4,**  
Article no. P70-2053-A



**PE-ST-45,**  
Article no. P70-2054-A



**Safety storage depots for 200 liter drums can be found on page 146!**

Model	PE-ST-2	PE-ST-4	PE-ST-45
External dimensions W x D x H (mm)	1500 x 1100 x 2110	1560 x 1790 x 2110	1560 x 1790 x 2110
Internal dimensions W x D x H (mm)	1220 x 750 x 1330	1220 x 1380 x 1510	1220 x 1380 x 1330
Sump capacity (l)	236	242	450
Capacity, 200 liter drums	2 directly on PE perforated plate or euro-pallet	4 directly on PE perforated plate or chemical pallet	4 directly on PE perforated plate or chemical pallet
Max. load (kg)	500	1000	1000
Article no., with PE perforated plate	P70-2052-A	P70-2053-A	P70-2054-A

### Accessory

Shelf set for storing small containers or canisters with 2 height-adjustable grid shelves, W x D x H (mm) = 1060 x 635 x 1150, max. load per shelf 200 kg

Article no.

**P70-2056-A**