



GEFAHRSTOFFSTATION FÜR KTC / IBC AUS PE

Zur Lagerung von wassergefährdenden und aggressiven Medien im Innen- oder Außenbereich

- ◆ Rotationsgeformte Konstruktion gelb, mit Wannenkörper aus PE schwarz
- ◆ Umlaufende Stabilisierungsrippen
- ◆ Unterfahrbarkeit für innerbetrieblichen Transport
- ◆ Stellebene aus PE-Lochplatte
- ◆ Doppelflügeltür abschließbar
- ◆ Auffangwannen mit allgemeiner bauaufsichtlicher Zulassung des DIBt Berlin
- ◆ Anlieferung als Bausatz zur einfachen Selbstmontage vor Ort

Zul.-Nr.: Z-40.22-451



PE-ST-KT, Artikel-Nr. P70-2055-A, mit Doppelflügeltür abschließbar



Sicherheitslagerhäuser für KTC / IBC finden Sie auf Seite 148/149!



PE-ST-KT, Artikel-Nr. P70-2055-A



PE-ST-KT, Artikel-Nr. P70-2055-A, mit optionaler Fasspalette

Typenbezeichnung	PE-ST-KT
Außenmaße B x T x H in mm	1770 x 1750 x 2260
Innenmaße B x T x H in mm	1450 x 1480 x 1320
Auffangvolumen in Liter	1000
Kapazität à KTC / IBC	1
Kapazität à 200-Liter-Fass stehend	4
Kapazität à 200-Liter-Fass liegend*	2
Max. Belastung in kg	2000
Artikel-Nr., mit PE-Lochplatte	P70-2055-A

* nur in Verbindung mit einer Fasspalette, Artikel-Nr. R67-1107-A möglich



PE STATION FOR KTC / IBC

For the storage of water-endangering and aggressive media indoors and outdoors

- ◆ Rotationally-molded PE-construction yellow, with black PE-sump tray
- ◆ Circumferential stabilizing ribs
- ◆ Ground clearance for internal transport
- ◆ PE perforated plate
- ◆ Double wing door lockable
- ◆ Sump trays with general technical approval DIBt Berlin
- ◆ Delivered as a kit for easy self-assembly on site

Approval-No.: Z-40.22-451



PE-ST-KT, Article no. P70-2055-A, with double wing door lockable



Safety storehouses for KTC / IBC can be found on page 146/147!



PE-ST-KT, Article no. P70-2055-A



PE-ST-KT, Article no. P70-2055-A, with optional drum pallet

Model	PE-ST-KT
External dimensions W x D x H (mm)	1770 x 1750 x 2260
Internal dimensions W x D x H (mm)	1450 x 1480 x 1320
Sump capacity (l)	1000
Capacity, KTC / IBC	1
Capacity, 200 liter drum vertical	4
Capacity, 200 liter drum horizontal*	2
Max. load (kg)	2000
Article no., with PE perforated plate	P70-2055-A

* possible only in combination with a drum pallet, Article no. R67-1107-A