



Erläuterungen siehe Praxisinfos auf den Seiten 6 und 86!


PFLANZENSCHUTZMITTELSCHRÄNKE BAUHÖHE 1000 / 1950 MM

Zur Lagerung von wassergefährdenden Pflanzenschutzmitteln in Kleingebinden im Gebäude

- ◆ Aus Qualitätsstahlblech
- ◆ Pulverbeschichtet RAL 6011 - resedagrün
- ◆ Türen verstärkt, mit Griffzylinderschloss
- ◆ Höhenverstellbare Ebenen
- ◆ Lüftungsöffnungen in den Türen
- ◆ Bauhöhe 1000 standardmäßig mit 2 Lagerebenen
- ◆ Bauhöhe 1950 standardmäßig mit 4 Lagerebenen
- ◆ Auffangwanne (AW) aus 3 mm Stahlblech, verzinkt -

Ü-Zeichen gemäß StawaR

- ◆ Wannböden (WB), verzinkt, flüssigkeitsdicht verschweißt, Tragkraft 50 kg
- ◆ Kennzeichnung nach ASR A1.3



PSM 500-1000 P, Artikel-Nr. B80-6554-A



PSM 500-1000 P, Artikel-Nr. B80-6554-A



PSM 1000-1000 P, Artikel-Nr. B80-6556-A



PSM 1000-1000 P, Artikel-Nr. B80-6556-A



PSM 500 P, Artikel-Nr. B80-6555-A



PSM 1000 P, Artikel-Nr. B80-6557-A

Schranktyp	PSM 500-1000 P	PSM 500 P	PSM 1000-1000 P	PSM 1000 P
Außenmaße B x T x H in mm	500 x 500 x 1000	500 x 500 x 1950	1000 x 500 x 1000	1000 x 500 x 1950
Ausführung	1-türig	1-türig	2-türig	2-türig
Auffangvolumen in Liter	AW 1 x 20 / WB 1 x 20	AW 1 x 20 / WB 3 x 20	AW 1 x 30 / WB 1 x 20	AW 1 x 30 / WB 3 x 20
Gewicht in kg	31	54	49	78
Artikel-Nr., RAL 6011	B80-6554-A	B80-6555-A	B80-6556-A	B80-6557-A

Zubehör	Artikel-Nr.	Artikel-Nr.	Artikel-Nr.	Artikel-Nr.
Wannenboden, Stahlblech, verzinkt	B80-6558-A	B80-6558-A	B80-6559-A	B80-6559-A
PE-Einsatz für Auffangwanne, zum Lagern von aggressiven Medien	B80-6560-A	B80-6560-A	B80-6561-A	B80-6561-A
PE-Einsatz für Wannböden, zum Lagern von aggressiven Medien	B80-6562-A	B80-6562-A	B80-6563-A	B80-6563-A



Explanations see practical informations on page 6 and 84!

CABINETS FOR PESTICIDES HEIGHT 1000 / 1950 MM

For storage of water-endangering pesticides in small containers indoors

- ◆ Made from high quality sheet steel
- ◆ Powder-coated in RAL 6011 - reseda green
- ◆ Doors reinforced, with handle cylinder lock
- ◆ Height-adjustable storage levels
- ◆ Ventilation slots in the doors
- ◆ Cabinets 1000 mm height with 2 storage levels
- ◆ Cabinets 1950 mm height with 4 storage levels
- ◆ Base sump tray (AW) made from 3 mm sheet steel, galvanized
 - **Ü-sign according to StawaR**
- ◆ Bottoms of tray-shaped shelves (WB), galvanized, are liquid-tight welded, max. load capacity 50 kg
- ◆ Marking according to ASR A1.3



PSM 500-1000 P,
Article no. B80-6554-A



PSM 500-1000 P,
Article no. B80-6554-A



PSM 1000-1000 P,
Article no. B80-6556-A



PSM 1000-1000 P,
Article no. B80-6556-A



PSM 500 P,
Article no. B80-6555-A



PSM 1000 P,
Article no. B80-6557-A

Model	PSM 500-1000 P	PSM 500 P	PSM 1000-1000 P	PSM 1000 P
External dimensions W x D x H (mm)	500 x 500 x 1000	500 x 500 x 1950	1000 x 500 x 1000	1000 x 500 x 1950
Door(s)	1	1	2	2
Sump capacity (l)	AW 1 x 20 / WB 1 x 20	AW 1 x 20 / WB 3 x 20	AW 1 x 30 / WB 1 x 20	AW 1 x 30 / WB 3 x 20
Weight (kg)	31	54	49	78
Article no., RAL 6011	B80-6554-A	B80-6555-A	B80-6556-A	B80-6557-A

Accessories	Article no.	Article no.	Article no.	Article no.
Tray-shaped shelf, sheet steel, galvanized	B80-6558-A	B80-6558-A	B80-6559-A	B80-6559-A
PE-insert for base sump tray, for storage of aggressive media	B80-6560-A	B80-6560-A	B80-6561-A	B80-6561-A
PE-insert for tray-shaped shelf, for storage of aggressive media	B80-6562-A	B80-6562-A	B80-6563-A	B80-6563-A